# **COLOROBBIA**

# SAFETY DATA SHEET

COLOROBBIA ITALIA			HCE000098					
S.P.A.								
Date of printing	:	15.12.2025	Date of issue	:	16.11.2024	Version	:	2.1

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 - Italy

# **SECTION 1: Identification of the substance/mixture and of the company/undertaking**

#### 1.1 Product identifier

Product name : HCE--000098

Product code : 00000000010100872 Other means of identification : HCE--000098-H002

# 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Third firing decoration in the glass/ceramics/porcelain sectorsThird

firing decoration in the glass/ceramics/porcelain sectors

Uses advised against

Not applicable.

# 1.3 Details of the supplier of the safety data sheet

COLOROBBIA ITALIA S.P.A. Indirizzo via Pietramarina 53 Località e Stato 50053 Sovigliana - Vinci (FI) Italia

tel. +39 0571 7091

fax +39 0571 709.850

e-mail address of person : responsible for this SDS

National advisory body/Poison Center

OHSE@colorobbia.it

# 1.4 Emergency telephone number

**Telephone number** : CAV - Ospedale Pediatrico Bambino Gesù - Roma - tel. +39 06

68593726

Az. Ospedaliera Università Foggia - Foggia - tel. 800183459 Az. Ospedaliera - A. Cardarelli- Napoli- tel. +39 081 7472870 CAV - Policlinico Umberto I- Roma - tel. +39 06 49978000 CAV - Policlinico A. Gemelli - Roma - tel. +39 06 3054343



Az. Ospedaliera Careggi - U.O. Tossicologia Medica - Firenze - tel. +39 055 7947819

CAV - Centro Nazionale di Informazione Tossicologica - Pavia - tel. +39 0382 24444

Ospedale Niguarda Ca' Granda - Milano - tel. +39 02 66101029 Az. ospedaliera Papa Giovanni XXIII - Bergamo - tel. 800883300

# **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

# Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT RE 1, H372 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

#### 2.2 Label elements

Hazard pictograms











Signal word : Danger

**Hazard statements** : H226 Flammable liquid and vapor.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H372 Causes damage to organs through prolonged or repeated

exposure.

H410 Very toxic to aquatic life with long lasting effects.

## **Precautionary statements**

General : Dispose of contents and container in accordance with all local,

regional, national and international regulations.

**Prevention**: Wear protective gloves. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking. Avoid release to the environment. Do not breathe vapor. Do not eat, drink or smoke when using this product. Wash your hands thoroughly after use (especially parts of the body



that may have been in contact with the product).

Response

Storage Not applicable.

Disposal Dispose of contents and container in accordance with all local,

regional, national and international regulations.

**Hazardous ingredients** bornan-2-one

formaldehyde, reaction products with butylphenol

eugenol turpentine, oil dodecane-1-thiol

linalool (E)-anethole

4-methylpentan-2-one

cineole

Eucalyptus globulus, ext. (R)-p-mentha-1,8-diene

pin-2(3)-ene

Supplemental label elements Not applicable.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures

Not applicable.

**Special packaging requirements** 

Containers to be fitted with child-resistant fastenings

Yes, applicable.

Tactile warning of danger Yes, applicable.

#### 2.3 Other hazards

and articles

for PBT or vPvB

**Product meets the criteria**: This mixture does not contain any substances that are assessed to be a PBT or a

vPvB.

according to Regulation (EC) No. 1907/2006,

**Annex XIII** 

Other hazards which do

: None known.

not result in classification

# **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M- factors and ATEs	Туре
bornan-2-one		>= 10 - <= 25	Flam. Sol. 2, H228		
	EC: 200-945-0		Skin Sens. 1, H317	-	

Version: 2.1 Date of issue/Date of revision: 16.11.2024 06.07.2024 Date of previous issue:



	CAS: 76-22-2		STOT RE 1, H372 Aquatic Chronic 4, H413		
rosin	EC: 232-475-7 CAS: 8050-09-7 Index: 650-015-00-7	>= 10 - <= 25	Met. Corr. 1, H290 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M [Acute] = 100 M [Chronic] = 10	
cyclohexanol	EC: 203-630-6 CAS: 108-93-0 Index: 603-009-00-3	>= 10 - < 20	Acute Tox. 4, H302 Acute Tox. 4, H332 Skin Irrit. 2, H315 STOT SE 3, H335 (Respiratory tract irritation)	ATE [Oral] = 1.400 mg/kg ATE [Inhalation (vapours)] = 11 mg/l	
formaldehyde, reaction products with butylphenol	EC: 294-145-9 CAS: 91673-30-2 Index: 605-021-00-4	> 0 - <= 10	Skin Sens. 1, H317	-	
eugenol	EC: 202-589-1 CAS: 97-53-0	> 0 - <= 10	Acute Tox. 4, H302 Eye Irrit. 2, H319 Skin Sens. 1, H317	ATE [Oral] = 1.930 mg/kg	
turpentine, oil	EC: 232-350-7 CAS: 8006-64-2 Index: 650-002-00-6	> 0 - <= 5	Flam. Liq. 3, H226 Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Asp. Tox. 1, H304 Aquatic Chronic 2, H411	ATE [Oral] = 500 mg/kg ATE [Dermal] = 1.100 mg/kg ATE [Inhalation (vapours)] = 13,7 mg/l	
dodecane-1-thiol	EC: 203-984-1 CAS: 112-55-0	> 0 - < 1	Skin Irrit. 2, H315 Eye Dam. 1, H318 Resp. Sens. 1, H334 Skin Sens. 1, H317 STOT SE 3, H335 (Respiratory tract irritation)	-	
linalool	EC: 201-134-4 CAS: 78-70-6 Index: 603-235-00-2	> 0 - < 1	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317	-	
(E)-anethole	EC: 224-052-0 CAS: 4180-23-8	> 0 - < 1	Skin Sens. 1, H317	-	
4-methylpentan-2-one	EC: 203-550-1 CAS: 108-10-1 Index: 606-004-00-4	> 0 - < 0,3	Flam. Liq. 2, H225 Acute Tox. 4, H332 Eye Irrit. 2, H319 Carc. 2, H351 STOT SE 3, H336	ATE [Inhalation (vapours)] = 11 mg/l	



			(Narcotic effects)		
cineole	EC: 207-431-5 CAS: 470-82-6	> 0 - <= 0,3	Flam. Liq. 3, H226 Skin Sens. 1, H317	-	
Eucalyptus globulus, ext.	EC : 283-406-2 CAS : 84625-32-1	> 0 - <= 0,3	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411	-	
(R)-p-mentha-1,8-diene	EC: 227-813-5 CAS: 5989-27-5 Index: 601-096-00-2	> 0 - <= 0,3	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1B, H317 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 3, H412	M [Acute] = 1	
pin-2(3)-ene	EC : 201-291-9 CAS : 80-56-8	> 0 - <= 0,3	Flam. Liq. 3, H226 Skin Sens. 1, H317 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M [Acute] = 1 M [Chronic] = 1	
camphene	EC : 201-234-8 CAS : 79-92-5	> 0 - <= 0,3	Flam. Sol. 2, H228 Eye Irrit. 2, H319 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M [Acute] = 1 M [Chronic] = 1	

See Section 16 for the full text of the H statements declared above. There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

#### **Type**

Substance classified with a health or environmental hazard

Occupational exposure limits, if available, are listed in Section 8.

# **SECTION 4: First aid measures**

## **4.1** Description of first aid measures

Eye contact

: Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.

Inhalation

: Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give



mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing

and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash

clothing before reuse. Clean shoes thoroughly before reuse.

Get medical attention immediately. Call a poison center or physician. **Ingestion** 

> Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway.

Loosen tight clothing such as a collar, tie, belt or waistband.

**Protection of first-aiders** No action shall be taken involving any personal risk or without

> suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

# 4.2 Most important symptoms and effects, both acute and delayed

# Over-exposure signs/symptoms

Skin contact

Eye contact Adverse symptoms may include the following: pain, watering,

redness

Inhalation No specific data.

Adverse symptoms may include the following: pain or irritation, Skin contact

redness, blistering may occur

**Ingestion** Adverse symptoms may include the following: stomach pains

# 4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Contact poison treatment specialist Notes to physician

immediately if large quantities have been ingested or inhaled.

**Specific treatments** No specific treatment.

# **SECTION 5: Firefighting measures**

# 5.1 Extinguishing media

Suitable extinguishing media Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.

Unsuitable extinguishing media Do not use water jet.

#### 5.2 Special hazards arising from the substance or mixture



Hazards from the substance or mixture

Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is very toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

**Hazardous combustion products** 

Decomposition products may include the following materials: carbon dioxide, carbon monoxide

## **5.3** Advice for firefighters

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

# **SECTION 6: Accidental release measures**

#### **6.1** Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**6.2** Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

#### 6.3 Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from



upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.

#### **6.4** Reference to other sections

See Section 1 for emergency contact information.
 See Section 8 for information on appropriate personal protective equipment.
 See Section 13 for additional waste treatment information.

# **SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 7.1 Precautions for safe handling

#### **Protective measures**

Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

# Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

## 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

# **Seveso Directive - Reporting thresholds**



# Danger criteria

Category	Notification and MAPP threshold	Safety report threshold
P5c	5.000 t	50.000 t
E1	100 t	200 t

## **7.3** Specific end use(s)

**Recommendations** : Not available. **Industrial sector specific** : Not available.

solutions

# **SECTION 8: Exposure controls/personal protection**

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

# **8.1** Control parameters

## **Occupational exposure limits**

Product/ingredient name	Exposure limit values
4-methylpentan-2-one	EU OEL (2000-06-01).
	TWA 83 mg/m3 20 ppm
	STEL 208 mg/m3 50 ppm
	Legislative Decree No. 819/2008. Title IX. Protection from chemical
	agents, carcinogens and mutagens (2004-03-01).
	TWA 83 mg/m3 20 ppm
	STEL 208 mg/m3 50 ppm

# **Biological exposure indices**

No exposure indices known.

# Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance



documents for methods for the determination of hazardous substances will also be required.

# **DNELs/DMELs**

Product/ingredient name	Type	Exposure	Value	Population	Effects
bornan-2-one	DNEL	Long term	4,3478	General	Systemic
		Inhalation	mg/m³	population	
	DNEL	Long term	17,6316	Workers	Systemic
		Inhalation	mg/m³		
	DNEL	Long term	5 mg/kg	General	Systemic
	D) 151	Dermal	bw/day	population	
	DNEL	Long term	5 mg/kg	General	Systemic
	DMEI	Oral	bw/day	population Workers	C
	DNEL	Long term Dermal	10 mg/kg bw/day	workers	Systemic
cyclohexanol	DNEL	Long term	1,43 mg/kg	Workers	Systemic
Cyclonexanol	DNEL	Dermal	bw/day	WOIKEIS	Systemic
	DNEL	Long term	0,716 mg/kg	General	Systemic
	DIVLL	Dermal	bw/day	population	Bysteine
	DNEL	Long term	0,716 mg/kg	General	Systemic
	21,22	Oral	bw/day	population	
	DNEL	Long term	40,3 mg/m <sup>3</sup>	Workers	Systemic
		Inhalation	, ,		
	DNEL	Long term	10 mg/m <sup>3</sup>	General	Systemic
		Inhalation		population	
rosin	DNEL	Long term	1,0655 mg/kg	General	Systemic
		Oral	bw/day	population	
	DNEL	Long term	10 mg/m³	Workers	Local
		Inhalation			
	DNEL	Long term	2,131 mg/kg	Workers	Systemic
1	DMEI	Dermal	bw/day	C 1	G
eugenol	DNEL	Long term Oral	3 mg/kg	General	Systemic
	DNEL	Long term	bw/day 21,2 mg/m³	population Workers	Systemic
	DNEL	Inhalation	21,2 mg/m²	WOIKEIS	Systemic
	DNEL	Long term	5,22 mg/m <sup>3</sup>	General	Systemic
	DIVLL	Inhalation	3,22 mg/m	population	Bysteine
	DNEL	Long term	3 mg/kg	General	Systemic
	·	Dermal	bw/day	population	
	DNEL	Long term	6 mg/kg	Workers	Systemic
		Dermal	bw/day		
turpentine, oil	DNEL	Short term	1,6 mg/kg	Workers	Systemic
		Dermal	bw/day		
	DNEL	Long term	0,11 mg/kg	General	Systemic
		Oral	bw/day	population	
	DNEL	Short term	51,6 mg/m <sup>3</sup>	Workers	Systemic
	DNE	Inhalation	10.2 / 2	XX7 1	T 1
	DNEL	Short term	10,3 mg/m <sup>3</sup>	Workers	Local
	DNEI	Inhalation	2.0 m s/3	Works	Local
	DNEL	Long term Inhalation	3,9 mg/m <sup>3</sup>	Workers	Local
	DNEI		2 17 mg/am²	Workers	Local
	DNEL	Long term	3,17 mg/cm <sup>2</sup>	Workers	Local



		Dermal			
	DNEL	Short term	0,59 mg/kg	General	Systemic
	DIVEL	Oral	bw/day	population	Systemic
	DNEL	Short term	$0.12 \text{ mg/m}^3$	General	Systemic
	BIVEE	Inhalation	0,12 mg/m	population	Systemic
	DNEL	Short term	9,51 mg/cm <sup>2</sup>	Workers	Local
	DIVEE	Dermal	),31 mg/cm	Workers	Locui
	DNEL	Long term	0,78 mg/m <sup>3</sup>	Workers	Systemic
	DIVEE	Inhalation	0,70 mg/m	Workers	Systemic
	DNEL	Long term	1,17 mg/kg	Workers	Systemic
	BIVEE	Dermal	bw/day	,, olicis	Systemic
	DNEL	Long term	$0.018 \text{ mg/m}^3$	General	Systemic
		Inhalation	7,010 11-8,111	population	2 3 3 3 3 3 3 3 3
	DNEL	Long term	0,417 mg/kg	General	Systemic
		Dermal	bw/day	population	
linalool	DNEL	Long term	3 mg/cm <sup>2</sup>	Workers	Local
		Dermal			
(E)-anethole	DNEL	Long term	3 mg/kg	Workers	Systemic
		Dermal	bw/day		
	DNEL	Long term	1,5 mg/kg	General	Systemic
		Dermal	bw/day	population	
	DNEL	Long term	1,5 mg/kg	General	Systemic
		Oral	bw/day	population	
	DNEL	Long term	2,61 mg/m <sup>3</sup>	General	Systemic
		Inhalation		population	
4-methylpentan-2-one	DNEL	Long term	4,2 mg/kg	General	Systemic
• •		Oral	bw/day	population	
	DNEL	Short term	208 mg/m <sup>3</sup>	Workers	Systemic
		Inhalation			
	DNEL	Short term	208 mg/m <sup>3</sup>	Workers	Local
		Inhalation			
	DNEL	Long term	83 mg/m <sup>3</sup>	Workers	Systemic
		Inhalation			
	DNEL	Long term	83 mg/m <sup>3</sup>	Workers	Local
		Inhalation			
	DNEL	Long term	14,7 mg/m <sup>3</sup>	General	Systemic
		Inhalation		population	
	DNEL	Long term	14,7 mg/m <sup>3</sup>	General	Local
		Inhalation		population	
	DNEL	Long term	11,8 mg/kg	Workers	Systemic
		Dermal	bw/day		
	DNEL	Short term	155,2 mg/m <sup>3</sup>	General	Systemic
		Inhalation		population	
	DNEL	Short term	155,2 mg/m³	General	Local
		Inhalation		population	
cineole	DNEL	Long term	1 mg/kg	General	Systemic
		Dermal	bw/day	population	
	DNEL	Long term	600 mg/kg	General	Systemic
		Oral	bw/day	population	
	DNEL	Long term	$7,05 \text{ mg/m}^3$	Workers	Systemic
		Inhalation			
	DNEL	Long term	2 mg/kg	Workers	Systemic
		Dermal	bw/day		



	DNEL	Long term Inhalation	1,74 mg/m³	General population	Systemic
Eucalyptus globulus, ext.	DNEL	Long term Inhalation	3,52 mg/m³	Workers	Systemic
	DNEL	Long term Dermal	1 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Dermal	0,5 mg/kg bw/day	General population	Systemic
	DNEL	Long term Oral	0,5 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	0,87 mg/m <sup>3</sup>	General population	Systemic
(R)-p-mentha-1,8-diene	DNEL	Long term Inhalation	16,6 mg/m³	General population	Systemic
	DNEL	Long term Dermal	9,5 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Dermal	4,8 mg/kg bw/day	General population	Systemic
	DNEL	Long term Oral	4,8 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	66,7 mg/m <sup>3</sup>	Workers	Systemic
pin-2(3)-ene	DNEL	Long term Dermal	0,225 mg/kg bw/day	General population	Systemic
	DNEL	Long term Oral	0,225 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	3,8 mg/m³	Workers	Systemic
	DNEL	Long term Inhalation	0,674 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Dermal	0,542 mg/kg bw/day	Workers	Systemic
camphene	DNEL	Long term Inhalation	110,19 mg/m³	Workers	Systemic
	DNEL	Short term Inhalation	110,19 mg/m³	Workers	Systemic
	DNEL	Long term Inhalation	54,3 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Short term Inhalation	54,3 mg/m³	General population	Systemic
	DNEL	Short term Dermal	1,25 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Dermal	0,625 mg/kg bw/day	General population	Systemic
	DNEL	Short term Oral	0,625 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0,1 mg/kg bw/day	General population	Systemic
	DNEL	Long term Oral	0,1 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0,21 mg/kg bw/day	Workers	Systemic



#### **PNECs**

No PNECs available.

#### **8.2** Exposure controls

Appropriate engineering controls

Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

# **Individual protection measures**

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

It is recommended to wear a hooded visor or protective visor combined with airtight goggles (ref. Standard EN 166).

# Skin protection

**Hand protection** 

: Protect hands with category III work gloves (ref. Standard EN 374). For the final choice of the material of the work gloves it is necessary to consider: compatibility, degradation, breakage time and permeation. In the case of preparations, the resistance of work gloves to chemical agents must be checked before use as it is not foreseeable. Gloves have a wear time that depends on the duration and method of use.

**Body protection** 

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.

Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** 

Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. In case of exceeding the threshold value (e.g. TLV-TWA) of the substance or of one or more of the substances present in the product, it is recommended to wear a mask with type AX filter whose limit of use will be defined by the manufacturer (ref. . standard EN 14387). If there are gases or vapors of a different nature and / or gases or vapors with particles (aerosols, fumes, mists, etc.), combined filters must be provided. The use of respiratory protection means is necessary in case the technical measures adopted are not sufficient to limit the exposure of the worker to the threshold values taken into



consideration. The protection offered by the masks is however limited. In the event that the substance in question is odorless or its olfactory threshold is higher than the relative TLV-TWA and in the event of an emergency, wear an open-circuit compressed air breathing apparatus (ref. Standard EN 137) or a self-contained breathing apparatus. outdoor air (ref. EN 138 standard). For the correct choice of the respiratory protection device, refer to the EN 529 standard.

**Environmental exposure controls** 

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

# **SECTION 9: Physical and chemical properties**

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

# 9.1 Information on basic physical and chemical properties

#### **Appearance**

Physical state : liquid [liquid]
Color : Brown.
Odor : Aromatic.

**Odor threshold**: No results available. Do not provide information on the danger of

the product

Melting point/freezing point Initial boiling point and boiling

range

: < 10 °C (< 50 °F) : > 100 °C (> 212 °F)

Flammability : FLAMMABLE.

**Lower and upper explosion limit** : **Lower:** Not available.

Upper: Not available.

Flash point :  $35 \,^{\circ}\text{C} \, (95 \,^{\circ}\text{F})$ Auto-ignition temperature :  $270 \,^{\circ}\text{C} \, (518 \,^{\circ}\text{F})$ 

**Decomposition temperature** : Not available.

**Product** is non-polar/aprotic.

Viscosity : Dynamic : Not available.

**Kinematic**: Not available.

**Solubility in water** : insoluble

**Partition coefficient: n-**Not applicable. The product is a mixture

octanol/water



# Vapor pressure

•
_

Γ=	Γ
Ingredient name formaldehyde	<b>Vapor pressure</b> 5.181 hPa (@ 25 °C) (77
Tormaldenyde	°F) 1,2 hPa (@ 20 °C) (68 °F)
ethyl acetate	108,78 hPa (@ 22,02 °C) (71,64 °F)
ethanol	57,26 hPa (@ 19,6 °C) (67,3 °F)
propan-2-ol	44 hPa (@ 20 °C) (68 °F)
toluene	30,8885114 hPa (@ 21,11 °C) (70,00 °F)
4-methylpentan-2-one	21 hPa (@ 20 °C) (68 °F)
xylene	8,93 hPa (@ 21 °C) (70 °F)
pin-2(3)-ene	8,51 hPa (@ 25 °C) (77 °F) (EU A.4) 6,9 hPa (@ 20 °C) (68 °F) (OECD 104)
(-)-pin-2(3)-ene	8,51 hPa (@ 25 °C) (77 °F) 6,9 hPa (@ 20 °C) (68 °F)
turpentine, oil	6,69 hPa (@ 25 °C) (77 °F) (EU A.4) 26 hPa (@ 25 °C) (77 °F) 5,19 hPa (@ 20 °C) (68 °F) (OECD 104)
cyclohexanone	5 hPa (@ 20 °C) (68 °F)
pin-2(10)-ene	3,54 hPa (@ 25 °C) (77 °F) (EU A.4) 2,73 hPa (@ 20 °C) (68 °F) (OECD 104)
dodecane-1-thiol	3,3 hPa (@ 25 °C) (77 °F)
(R)-p-mentha-1,8-diene	2 hPa (@ 24,85 °C) (76,73 °F)
1-isopropyl-4-methylbenzene	2 hPa (@ 20 °C) (68 °F)
p-mentha-1,4(8)-diene	1,33 hPa (@ 25 °C) (77 °F) 1,01 hPa (@ 20 °C) (68 °F)
cyclohexanol	1,3 hPa (@ 20 °C) (68 °F) 1,33 hPa
cineole	1,22 hPa (@ 20 °C) (68 °F)
001-	0,87 hPa (@ 25 °C) (77 revious issue: 06.07.2024
3-methoxybutyl acetate	5 hPa (@ 50 °C) (122 °F) (OECD 104) 0,34 hPa (@ 20 °C) (68 °F) (OECD 104) 0,58 hPa (@ 25 °C) (77 °F) (OECD 104)

Version: 2.1 Date of issue/Date of

		°F)
f	bornan-2-one revision: 16.11.2024 Date of p	0,87 hPa (@ 25 °C) (77 resipus issue: 06.07.2024
	3-methoxybutyl acetate	5 hPa (@ 50 °C) (122 °F) (OECD 104) 0,34 hPa (@ 20 °C) (68 °F) (OECD 104) 0,58 hPa (@ 25 °C) (77 °F) (OECD 104)
	benzyl alcohol	0,33 hPa (@ 25 °C) (77 °F) 0,07 hPa (@ 20 °C) (68 °F)

0,98 Relative density

0,85 - 1,1 g/cm3 **Density** > 1 [Air = 1]Vapor density **Explosive properties** Not available. **Oxidizing properties** Not available.

**Particle characteristics** 

Median particle size Not applicable.

# **SECTION 10: Stability and reactivity**

No specific test data related to reactivity available for this product or **10.1** Reactivity its ingredients.

**10.2** Chemical stability The product is stable.

10.3 Possibility of hazardous Under normal conditions of storage and use, hazardous reactions reactions will not occur.

10.4 Conditions to avoid Avoid all possible sources of ignition (spark or flame). Do not

pressurize, cut, weld, braze, solder, drill, grind or expose containers

to heat or sources of ignition.

Reactive or incompatible with the following materials: oxidizing **10.5** Incompatible materials

materials

**10.6** Hazardous decomposition Under normal conditions of storage and use, hazardous products

decomposition products should not be produced.

# **SECTION 11: Toxicological information**

# 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

# **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
cyclohexanol				
	LD50 Oral	Rat	1.400 mg/kg	-
rosin				
	LD50 Oral	Rat	7.600 mg/kg	-
eugenol				
	LD50 Oral	Rat	1.930 mg/kg	-
turpentine, oil				
	LD50 Oral	Rat	3.956 mg/kg	-
	LC50 Inhalation	Rat	19,9 mg/l	1 h

2.1 Date of issue/Date of revision: 16.11.2024 06.07.2024 Version: Date of previous issue:



	Vapor			
	Vapor LC50 Inhalation Vapor	Rat	13,7 mg/l	4 h
linalool				
	LD50 Oral	Rat	2.790 mg/kg	-
	LD50 Dermal	Rabbit	5.610 mg/kg	-
	LD50 Dermal	Rat	5.610 mg/kg	-
(E)-anethole				
	LD50 Oral	Rat	2.090 mg/kg	-
4-methylpentan-2-one				
	LD50 Oral	Rat	2.080 mg/kg	-
cineole	•			•
	LD50 Oral	Rat	2.480 mg/kg	-
(R)-p-mentha-1,8-diene	1	•		•
	LD50 Oral	Rat	4.400 mg/kg	-
	LD50 Dermal	Rabbit	5.000 mg/kg	-
pin-2(3)-ene	1			•
	LD50 Oral	Rat	3.700 mg/kg	-
	LD50 Dermal	Rabbit	5.000 mg/kg	-
camphene	•			•
•	LD50 Oral	Rat	5.000 mg/kg	-
	LC50 Inhalation	Rat	17,1 mg/l	1 h
	Vapor			
	LC50 Inhalation	Rat	17,1 mg/l	4 h
	Vapor			

Conclusion/Summary :

# **Acute toxicity estimates**

Product/ingredient name	Oral	Dermal	Inhalation (gases)	Inhalation (vapors)	Inhalation (dusts and mists)
HCE000098-H002	4479,5 mg/kg	29640 mg/kg	N/A	57,1 mg/l	N/A
cyclohexanol	1400 mg/kg	N/A	N/A	11 mg/l	N/A
rosin	7600 mg/kg	N/A	N/A	N/A	N/A
eugenol	1930 mg/kg	N/A	N/A	N/A	N/A
turpentine, oil	500 mg/kg	1100 mg/kg	N/A	13,7 mg/l	N/A
linalool	2790 mg/kg	5610 mg/kg	N/A	N/A	N/A
(E)-anethole	2090 mg/kg	N/A	N/A	N/A	N/A
4-methylpentan-2-one	500 mg/kg	N/A	N/A	11 mg/l	N/A
cineole	2480 mg/kg	N/A	N/A	N/A	N/A
(R)-p-mentha-1,8-diene	4400 mg/kg	5000 mg/kg	N/A	N/A	N/A
pin-2(3)-ene	3700 mg/kg	5000 mg/kg	N/A	N/A	N/A
camphene	5000 mg/kg	N/A	N/A	N/A	N/A

Not available.



# **Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
cyclohexanol	Skin -	Rabbit	-	24 hrs	-
	Moderate				
	irritant				
	Skin - Mild	Rabbit	-	24 hrs	-
	irritant				
	Eyes -	Rabbit	-	24 hrs	-
	Moderate				
	irritant				
	Eyes - Mild	Rabbit	-	24 hrs	-
	irritant				
	Eyes -	Rabbit	-		-
	Moderate				
	irritant				
eugenol	Skin -	Man	-	48 hrs	-
	Moderate				
	irritant				
	Skin - Severe	Rabbit	-	24 hrs	-
	irritant				
	Skin - Mild	Pig	-	48 hrs	-
	irritant				
	Skin -	Guinea pig	-	24 hrs	-
	Moderate				
	irritant				
	Skin - Mild	Human	-	48 hrs	-
	irritant				
turpentine, oil	Skin - Severe	Rabbit	-		-
	irritant				
	Skin - Severe	Human	-		-
	irritant				
linalool	Eyes -	Rabbit	-	1 hrs	-
	Moderate				
	irritant				
	Skin - Mild	Man	-	48 hrs	-
	irritant				
	Skin - Mild	Rabbit	-	24 hrs	-
	irritant				
	Skin - Severe	Rabbit	-	24 hrs	-
	irritant				
	Eyes -	Rabbit	-		-
	Moderate				
	irritant				
	Skin -	Guinea pig	-	24 hrs	-
	Moderate				
	irritant				
	Skin - Mild	Human	-	72 hrs	-
	irritant				
4-methylpentan-2-one	Eyes -	Rabbit	-	24 hrs	-
	Moderate				
	irritant				
	Skin - Mild	Rabbit	-	24 hrs	-



	irritant				
	Eyes -	Rabbit	-		-
	Severe				
	irritant				
(R)-p-mentha-1,8-diene	Skin - Mild	Rabbit	-	24 hrs	-
	irritant				
pin-2(3)-ene	Skin -	Rabbit	-	24 hrs	-
	Moderate				
	irritant				
	Skin - Severe	Man	-		-
	irritant				

Conclusion/Summary

Skin: Not available.Eyes: Not available.Respiratory: Not available.

# **Sensitization**

Conclusion/Summary

Skin: Not available.Respiratory: Not available.

Mutagenicity

**Conclusion/Summary** : Not available.

Carcinogenicity

Conclusion/Summary : Not available.

Reproductive toxicity

Conclusion/Summary : Not available.

**Teratogenicity** 

**Conclusion/Summary** : Not available.

# Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
cyclohexanol	Category 3	=	Respiratory tract irritation
dodecane-1-thiol	Category 3	-	Respiratory tract irritation

# Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
bornan-2-one	Category 1	=	-

## **Aspiration hazard**

Product/ingredient name	Result
turpentine, oil	ASPIRATION HAZARD - Category 1
pin-2(3)-ene	ASPIRATION HAZARD - Category 1



Information on the likely routes

of exposure

Not available.

#### Potential acute health effects

**Eye contact** : Causes serious eye damage.

**Inhalation** : No known significant effects or critical hazards.

**Skin contact** : Causes skin irritation. May cause an allergic skin reaction.

**Ingestion** : No known significant effects or critical hazards.

# Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : Adverse symptoms may include the following: pain, watering,

redness

**Inhalation** : No specific data.

**Skin contact** : Adverse symptoms may include the following: pain or irritation,

redness, blistering may occur

**Ingestion**: Adverse symptoms may include the following: stomach pains

#### Delayed and immediate effects and also chronic effects from short and long term exposure

#### Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

#### Long term exposure

Potential immediate effects : Not available.
Potential delayed effects : Not available.

# Potential chronic health effects

**Conclusion/Summary** : Not available.

**General** : Causes damage to organs through prolonged or repeated exposure.

Once sensitized, a severe allergic reaction may occur when

subsequently exposed to very low levels.

Carcinogenicity: No known significant effects or critical hazards.Mutagenicity: No known significant effects or critical hazards.Reproductive toxicity: No known significant effects or critical hazards.

#### 11.2. Information on other hazards

**11.2.1 Endocrine disrupting properties** : Not available. **11.2.2 Other information** : Not available.

# **SECTION 12: Ecological information**

#### 12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
cyclohexanol			



	Acute LC50 704 mg/l Fresh	Fish - Pimephales promelas	96 h
	water	14sh - 1 inicpliates profficias	90 II
eugenol	water	1	
cugenor	Acute LC50 24 mg/l Fresh	Fish - Pimephales promelas	96 h
	water	Tish Timephates prometas	70 H
linalool	water	1	
maiooi	Acute LC50 28,8 mg/l Fresh	Fish - Oncorhynchus mykiss	96 h
	water	1 isii Oncornynenus mykiss	70 H
	Acute EC50 36,7 mg/l Fresh	Daphnia - Daphnia magna	48 h
	water	Dapinna - Dapinna magna	40 11
(E)-anethole	water	1	
(E)-anethore	Acute EC50 4,81 mg/l Fresh	Fish - Pimephales promelas	96 h
	water		
	Acute EC50 4,25 mg/l Fresh	Daphnia - Daphnia magna	48 h
	Acute IC50 9,313 mg/l Fresh	Algae - Pseudokirchneriella	96 h
		subcapitata	90 11
4-methylpentan-2-one	water	subcapitata	1
4-methylpentan-2-one	Acute LC50 505 mg/l Fresh	Fish - Pimephales promelas	96 h
	water	Fish - Filiephales profiletas	90 11
	Chronic NOEC 168 mg/l Fresh	Fish - Pimephales promelas	33 d
	water	14sh - 1 inicpliates profiletas	33 u
	Chronic NOEC 78 mg/l Fresh	Daphnia - Daphnia magna	21 d
	water	Dapinna - Dapinna magna	21 0
cineole	water	1	1
Cincole	Acute LC50 102 mg/l Fresh	Fish - Pimephales promelas	96 h
	water	Tish Timephates prometas	70 h
(R)-p-mentha-1,8-diene	Water	1	
(к) р шении 1,6 шене	Acute EC50 0,688 mg/l Fresh	Fish - Pimephales promelas	96 h
	water	Tish Timephates prometas	70 h
	Acute EC50 0,421 mg/l Fresh	Daphnia - Daphnia magna	48 h
	water	Dupinia Dupinia magna	10 11
pin-2(3)-ene	water		
p 2(0) one	Acute LC50 5,28 mg/l Fresh	Fish - Lepomis macrochirus	96 h
	water	Lepoints indercentus	"
	Acute LC50 41 mg/l Fresh	Daphnia - Daphnia magna	48 h
	water	Zapinia Dapinia magna	1011
camphene	1		1
P	Acute LC50 1,17 mg/l Fresh	Fish - Lepomis macrochirus	96 h
	water		1
	Acute LC50 22 mg/l Fresh	Daphnia - Daphnia magna	48 h
	water		1.0.11
	Acute EC50 214 mg/l Marine	Algae - Skeletonema	96 h
	water	costatum	"

**Conclusion/Summary** : Not available.

# **12.2** Persistence and degradability

Conclusion/Summary : Not available.

# 12.3 Bioaccumulative potential



Product/ingredient name	LogPow	BCF	Potential
bornan-2-one	2,38	-	low
cyclohexanol	1,21,25	-	low
rosin	1,9 - 7,7	-	high
eugenol	2,27	-	low
dodecane-1-thiol	6,5	-	high
linalool	2,84	-	low
4-methylpentan-2-one	1,9	-	low
cineole	2,74	-	low
(R)-p-mentha-1,8-diene	4,57	-	high
pin-2(3)-ene	4,487	-	high
camphene	-	954,99	high

#### 12.4 Mobility in soil

Soil/water partition coefficient

(KOC)

Not available.

**Mobility** : Not available.

#### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**12.6 Endocrine disrupting properties** : Not available.

**12.7 Other adverse effects** : No known significant effects or critical hazards.

# **SECTION 13: Disposal considerations**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 13.1 Waste treatment methods

## **Product**

**Methods of disposal** : The generation of waste should be avoided or minimized wherever

possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the

requirements of all authorities with jurisdiction.

**Hazardous waste**: The classification of the product may meet the criteria for a

hazardous waste.

# European waste catalogue (EWC)

Waste code	Waste designation
16 03 05*	organic wastes containing hazardous substances



# **Packaging**

Methods of disposal

: The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Type of packaging		European waste catalogue (EWC)
	15 01 10*	packaging containing residues of or contaminated by
		hazardous substances

# **Special precautions**

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

# **SECTION 14: Transport information**

	ADR/RID	IMDG	IATA
14.1 UN number	UN1993	UN1993	UN1993
14.2 UN proper shipping name	FLAMMABLE LIQUID, N.O.S.FLAMMABLE LIQUID, N.O.S. (turpentine, oil)	FLAMMABLE LIQUID, N.O.S.FLAMMABLE LIQUID, N.O.S. (turpentine, oil) Marine pollutant (rosin,turpentine, oil)	Flammable liquid, n.o.s.FLAMMABLE LIQUID, N.O.S. (turpentine, oil)
14.3 Transport hazard class(es)	3	3	3
14.4 Packing group	III	III	III
14.5. Environmental hazards	Yes.	Yes.	Yes. The environmentally hazardous substance mark is not required.

# Additional information

ADR/RID

: The environmentally hazardous substance mark is not required when transported in sizes of  $\leq$ 5 L or  $\leq$ 5 kg.

**Tunnel code** (D/E)

**ADN** 

: The environmentally hazardous substance mark is not required when transported in sizes of  $\leq$ 5 L or  $\leq$ 5 kg.

**IMDG** 

: The marine pollutant mark is not required when transported in sizes of  $\leq$ 5 L or  $\leq$ 5 kg.



**IATA** 

The environmentally hazardous substance mark may appear if required by other transportation regulations.

14.6 Special precautions for user

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according

: Not available.

to IMO instruments

# **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

## EU Regulation (EC) No. 1907/2006 (REACH)

# Annex XIV - List of substances subject to authorization

#### **Annex XIV**

None of the components are listed.

#### Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles Not applicable.

# **Other EU regulations**

**Industrial emissions (integrated** 

pollution prevention

and control) - Air

**Industrial emissions (integrated** 

Not listed

Not listed

pollution prevention and control) - Water

# Ozone depleting substances (1005/2009/EU)

None of the components are listed.

# Prior Informed Consent (PIC) (649/2012/EU)

None of the components are listed.

# Persistent Organic Pollutants

None of the components are listed.

#### Seveso Directive

This product is controlled under the Seveso Directive.

# Danger criteria

Category

P5c



E1

### National regulations

**D.Lgs. 152/06** : Not determined.

**International regulations** 

#### Chemical Weapon Convention List Schedules I, II & III Chemicals

# **Chemical Weapons Convention List Schedule I Chemicals**

None of the components are listed.

#### **Chemical Weapons Convention List Schedule II Chemicals**

None of the components are listed.

# **Chemical Weapons Convention List Schedule III Chemicals**

None of the components are listed.

# **Montreal Protocol**

None of the components are listed.

#### **Stockholm Convention on Persistent Organic Pollutants**

# **Annex A - Elimination - Production**

None of the components are listed.

# **Annex A - Elimination - Use**

None of the components are listed.

# **Annex B - Restriction - Production**

None of the components are listed.

# **Annex B - Restriction - Use**

None of the components are listed.

# **Annex C - Unintentional - Production**

None of the components are listed.

# Rotterdam Convention on Prior Informed Consent (PIC)

# Rotterdam Convention on Prior Informed Consent (PIC) - Industrial

None of the components are listed.

## Rotterdam Convention on Prior Informed Consent (PIC) - Pesticide

None of the components are listed.

# Rotterdam Convention on Prior Informed Consent (PIC) -Severely hazardous pesticide

None of the components are listed.

# **UNECE Aarhus Protocol on POPs and Heavy Metals**

## Heavy metals - Annex 1

None of the components are listed.



#### POPs - Annex 1 - Production

None of the components are listed.

#### POPs - Annex 1 - Use

None of the components are listed.

## POPs - Annex 2

None of the components are listed.

# POPs - Annex 3

None of the components are listed.

## **Inventory list**

Australia: Not determined.Canada: Not determined.China: Not determined.

**Eurasian Economic Union** 

**Japan inventory** (CSCL): Not determined.

Japan inventory (ISHL): Not determined.

**New Zealand** Not determined. **Philippines** Not determined. Republic of Korea Not determined. **Taiwan** Not determined. **Thailand** Not determined. Not determined. **Turkey United States** Not determined. Viet Nam Not determined.

15.2 Chemical Safety Assessment

This product contains substances for which Chemical Safety

Assessments are still required.

# **SECTION 16: Other information**

**Abbreviations and acronyms** : ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation

[Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

N/A = Not available


PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

SGG = Segregation Group

vPvB = Very Persistent and Very Bioaccumulative

# Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Flam. Liq. 3, H226	On basis of test data





Skin Irrit. 2, H315	Calculation method
Eye Dam. 1, H318	Calculation method
Skin Sens. 1, H317	Calculation method
STOT RE 1, H372	Calculation method
Aquatic Acute 1, H400	Calculation method
Aquatic Chronic 1, H410	Calculation method

# Full text of abbreviated H statements

H225	Highly flammable liquid and vapor.
H226	Flammable liquid and vapor.
H228	Flammable solid.
H290	May be corrosive to metals.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if
	inhaled.
H335	May cause respiratory irritation.
H341	Suspected of causing genetic defects.
H360	May damage fertility or the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

# Full text of classifications [CLP/GHS]

Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	AQUATIC HAZARD (ACUTE) - Category 1
Aquatic Chronic 1	AQUATIC HAZARD (LONG-TERM) - Category 1
Aquatic Chronic 2	AQUATIC HAZARD (LONG-TERM) - Category 2
Aquatic Chronic 4	AQUATIC HAZARD (LONG-TERM) - Category 4
Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Eye Dam. 1	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2
Flam. Liq. 2	FLAMMABLE LIQUIDS - Category 2
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Flam. Sol. 2	FLAMMABLE SOLIDS - Category 2
Met. Corr. 1	CORROSIVE TO METALS - Category 1
Muta. 2	GERM CELL MUTAGENICITY - Category 2
Repr. 1B	TOXIC TO REPRODUCTION - Category 1B
Resp. Sens. 1	RESPIRATORY SENSITIZATION - Category 1
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITIZATION - Category 1
Skin Sens. 1B	SKIN SENSITIZATION - Category 1B



STOT RE 1	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) -
	Category 1
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) -
	Category 3

Date of printing: 15.12.2025Date of issue/ Date of revision: 16.11.2024Date of previous issue: 06.07.2024Version: 2.1

# Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Notwithstanding the above, the provisions of this clause shall not apply in the event of supplier wilful misconduct (dolo), in which case the provisions of current legislation shall apply.

